Rhodes®

MK8 Quickstart Guide

Dear MK8 owner,

Welcome to the Rhodes family.

Let us take this opportunity to thank you for purchasing the Rhodes MK8, the next generation of our classic tine piano. The MK8 builds upon our unique history whilst taking the Rhodes piano proudly into the future.

We sincerely hope this piano inspires your musical journey for many years to come.

Warm regards, The Rhodes Team

Built by Rhodes, Defined by You.



1. UNBOX YOUR MK8 AND REGISTER ONLINE

With another person, take your new MK8 out of the inner box and inspect for damage. Scan the QR code on the back of your **Rhodes** Members Club card - this will take you to the Rhodes Members Club area. Here you will find the MK8 manual, quick start setup videos, firmware updates and warranty information.





2. STAND ASSEMBLY

1. Remove the four legs and two **cross braces** from their holders. Screw each leg into the four corners (A) of the frame. 2. Attach the **cross braces (B)** to the inner bars using the **thumbscrews (C)**, next, unscrew the lower part of the rear legs (D) and slot in the cross braces. **Retighten the lower part of the rear legs.** Flip the stand over. 3. Loosen the **two thumbscrews (E)** and extend the frame so the straight edge of the square tube lines up with the point of the arrow (F). 4. With the help of another person, set the piano down onto the stand. 5. If placing the piano on an uneven surface, level the front legs using the adjustable feet.





3. AUDIO CONNECTIONS

FOR STEREO

Connect the MK8 stereo outputs using two 1/4 inch jack leads (1) or two XLR leads (2) to the inputs of a high-quality stereo amplifier, audio interface, mixing desk, or into two full-range mono amps/ active speakers.

FOR MONO

Connect the left output jack (3) or left XLR output (4) to your amp, speaker or audio interface.

FOR HEADPHONES

Use the built-in headphone output in the left cheek block on the front of the MK8. Use the rotary control to adjust the volume.



1/4 inch jack outputs (1) XLR outputs (2)





4. <u>power</u>

Connect the mains power cord to the included **MK8 universal voltage power adaptor.** Plug the **4-pin XLR power connector** into the MK8 power input **(1)**. Next, plug the mains cable into a power outlet. Flick the power switch to ON **(2)**, turn up your monitoring equipment to a comfortable level and your MK8 is ready.

 \triangle

CAUTION: Please switch your MK8 on before powering on your monitoring equipment.



5. <u>preamp, volume and eq</u>

Set the main volume control to a comfortable level. To adjust the EQ, set the **LOW** and **HIGH** dials to taste.



6. PEDAL CONNECTION

- Place the pedal in your preferred position under the piano.
- Standing behind the piano, insert the twist-lock connector (A) into the underside of the piano.
- **3.** Turn the **twist-lock connector** fully anticlockwise until it locks firmly in place.
- Take the knurled connector

 (B) and pull it upwards whilst screwing it anticlockwise all the way onto the threaded push rod that protrudes from the underside of the piano. Your pedal is now connected.



2.

🗥 GENERAL SAFETY

- Ensure the pedal is removed before moving the piano.
- Do not allow children to use without supervision.
- Do not stack the piano (possible chance of falling).
- Please ensure that the piano is carried by a minimum of two people.

\triangle attention

For repairs or service please refer to a qualified Rhodes Service Centre or Technician. Please visit www.rhodesmusic.com for details.



support@rhodesmusic.com +44 (0) 113 824 6073

2B Meanwood Close, Leeds, LS7 2JL, UK Made in the UK.

\land WARNING

- Do not disassemble or modify.
- To reduce the risk of fire or electric shock do not expose this apparatus to rain or moisture.
- If you have wet hands, do not handle, connect, or disconnect the power cord.
- Remove the power cord from the AC outlet if there is a possibility of a lightning strike.
- Do not let foreign objects, such as flammable or conductive materials enter the piano.
- Do not allow liquid ingress of any kind.
- Do not store containers of liquid on the piano.
- Do not install the piano near heat sources.

\triangle caution

• When moving the piano, ensure all cables are removed (power, sustain pedal, headphones, USB, audio cables).

Rhodes[®]

RHODESMUSIC.COM

RHODES IS A REGISTERED TRADEMARK